



MH320 Portable Hardness Tester



Advantages

- Large screen(128×64 dot matrix LCD), showing all functions and parameters.
- Test at any angle, even upside down.
- Wide measuring range. It can measure the hardness of all metallic materials. Direct display of hardness scales HRB, HRC, HV, HB, HS, HL and three types of strength values immediately.

Saver AB
Gjutegården 161
S-436 45 ASKIM
SWEDEN



Tel: +46 (0) 31 28 28 89
Mobil: +46 (0) 707 415 428
Mail: bengt@se-saver.se
www.se-saver.se



- Seven impact devices are available for special application. Automatically identify the type of impact devices.
- Large capacity memory could store 500 groups (Relative to average times 32~1) information including single measured value, mean value, testing data, impact direction, impact times, material and hardness scale etc.
- Upper and lower limit can be preset. It will alarm automatically when the result value exceeding the limit.
- Battery information indicates the rest capacity of the battery and the charge status.
- User calibration function.
- USB port with the PC humanity multi-functions data proceeding software.
- Original imported high speed thermal printer support the immediate printing function. It can save data permanently.
- NI-MH rechargeable battery as the power source. Charge circuit integrated inside the instrument. Continuous working period of no less than 150 hours (EL off and no printing).
- Auto power off to save energy.
- Excellent after-sale service system for high quality products---two years' guarantee and all life maintenance. Easy to buy and comfortable to use.

Main Application

- Die cavity of molds
- Bearings and other parts
- Failure analysis of pressure vessel, steam generator and other equipment
- Heavy work piece
- The installed machinery and permanently assembled parts
- Testing surface of a small hollow space
- Material identification in the warehouse of metallic materials
- Rapid testing in large range and multi-measuring areas for large-scale work piece

Technical Specifications

- Measuring range: HLD (170~960) HLD
- Measuring direction: 360°
- Hardness Scale: HL、HB、HRB、HRC、HRA、HV、HS
- Display: dot matrix LCD, 128×64 dots
- Data memory: 500 groups max. (relative to impact times 32~1)

Saver AB
Gjutegården 161
S-436 45 ASKIM
SWEDEN



Tel: +46 (0) 31 28 28 89
Mobil: +46 (0) 707 415 428
Mail: bengt@se-saver.se
www.se-saver.se



- Printing paper: width is (57.5±0.5) mm, diameter is 30mm
- Battery pack: 6V NI-MH
- Battery charger: 9V/500mA
- Continuous working period: about 150 hours (With backlight off, no printing)
- Communication interface: USB1.1
- Outline dimensions: 212mm×80mm×32mm

Configuration

	No.	Item	Quantity	Remarks
Standard Configuration	1	Main Unit	1	
	2	D type impact device	1	With cable
	3	Standard test block	1	
	4	Cleaning brush (I)	1	
	5	Small support ring	1	
	6	Battery Charger	1	9V 500mA
	7	Paper for printing	1	
	8	Manual	1	
	9	DataPro software	1	
	10	Communication cable	1	
	11	Instrument case	1	
	12	Cleaning brush (II)	1	For use with G type impact device
	13	Other type of impact devices and support rings		Refer to Table 3 and Table 4 in the appendix.
	14			
	15			

Saver AB
 Gjutegården 161
 S-436 45 ASKIM
 SWEDEN



Tel: +46 (0) 31 28 28 89
 Mobil: +46 (0) 707 415 428
 Mail: bengt@se-saver.se
www.se-saver.se