



MT160 Ultrasonic Thickness Gauge



Overview

The model MT160 is a digital ultrasonic thickness gauge. Based on the principle of ultrasonic principle, the instrument is capable of measuring the thickness of various materials, such as metal, plastic, ceramic, glass and many other good ultrasonic conductors. It of all kinds of materials. Compared with the traditional measurement methods, the advantages of ultrasonic thickness gauge is exposed to one side of the workpiece to complete the measurement. Its unique non-destructive testing performance provide the perfect solution for the thickness testing of closed pipes, containers, etc. It is widely used in petroleum, chemical, metallurgy, shipbuilding, aviation, aerospace and other fields because of monitoring corrosion thinning degree of various pipes and pressure vessels. It can also be used for precise measurement of sheet metal and machined parts.

Technical Parameters

Display	4.5 digits LCD with EL backlight
Measuring Range	(0.75~300)mm (in Steel)
Sound Velocity Range	(1000~9999) m/s
Resolution	0.1mm/0.01mm

Accuracy	$\pm(0.5\% \text{Thickness} + 0.04)$ mm, depends on materials and conditions
Units	Metric/Imperial unit selectable
Measurement Frequency	Four measurements readings per second for single point measurement, and ten per second for Scan Mode
Storage	Memory for up to 20 files (up to 99 values for each file) of stored values
Thickness Measurement Modes	Single point thickness measurement and scanning thickness measurement
Power Source	Two "AA" size, 1.5 Volt alkaline batteries
Operating Time	More than 100 hours (EL backlight off)
Communication	USB1.1(Can communicate with PC)
Outline Dimension	150mm×74mm×32 mm
Weight	245g

Features

- Suitable for measuring metal (such as steel, cast iron, aluminum, copper, etc.) , plastics, ceramics, glass, fiber glass and any other good ultrasonic conductors;
- Dual straight beam probes with different frequencies and crystal sizes are available;
- Zero calibration, two-point calibration, automatic error correction system;
- Known thickness, sound speed can be measured, in order to improve the measurement accuracy;
- Coupling status indicator showing the coupling status;
- EL backlight for easy use in dimly lit environments;
- Remaining battery indicator can display the remaining power in real time;
- Auto sleep and auto power off function to conserve battery life
- Small, portable, high reliability for harsh operating environment, anti-vibration, anti-shock and anti-electromagnetic interference.

Working Principle

The digital ultrasonic thickness gauge determines the thickness of a part or structure by accurately measuring the time required for a short ultrasonic pulse generated by a transducer to travel through the thickness of the material, reflect from the back or inside surface, and be returned to the transducer. The measured two-way transit time is divided by two to account for the down-and-back travel path, and then multiplied by the velocity of sound in the material. The result is expressed in the well-known relationship.

	No.	Item	Quantity	Note
Standard Configuration	1	Main body	1	
	2	Probe: N05	1	
	3	Couplant	1	
	4	Instrument Case	1	
	5	Operating Manual	1	
	6	Alkaline battery	2	
Optional Configuration	1	Probe: N05/90°(5MHz)		
	2	Probe: N02(2.5MHz)		
	3	Probe: N07(7MHz)		
	4	Probe: HT5(5MHz)		
	5	High temperature couplant		
	6	USB Cable		
	7	DataPro Software		

Saver AB
Gjutegården 161
S-436 45 ASKIM
SWEDEN



Tel: +46 (0) 31 28 28 89
Mobil: +46 (0) 707 415 428
Mail: bengt@se-saver.se
www.se-saver.se